

I hereby certify that this paper or fee is being filed with the United States Patent and Trademark Office via EFS-Web under 37 CFR § 1.8 on the Date of Deposit indicated below.

Signed: Liesenia Rocha-Fernandez

Name: Liesenia Rocha-Fernandez

Date of Deposit: November 15, 2012

IN THE
UNITED STATES PATENT AND TRADEMARK OFFICE

APPL. NO.:	09/735,697	CONF. NO.:	6750
FILED:	DECEMBER 12, 2000	ART UNIT:	2836
APPLICANT:	NOEL LEE	EXAMINER:	DEBERADINIS, ROBERT L.
DOCK. NO.:	P1230	CUST. NO.:	24,394
TITLE:	APPARATUS AND METHOD FOR POWERING MULTIPLE PERIPHERAL DEVICES FROM A COLOR-CODED CENTRAL POWER SOURCE		

MAIL STOP AMENDMENTS
COMMISSIONER FOR PATENTS
PO BOX 1450
ALEXANDRIA VA 22313-1450

**RESPONSE TO NOTIFICATION OF NON-COMPLIANT
APPEAL BRIEF (37 CFR 41.37)**

To the Commissioner:

This is the corrected Section III of the Appeal Brief arising from the Second Notification of Non-Compliant Appeal Brief.

Respectfully Submitted,



John E. Nielsen
Patent Reg. No. 53,392

JEN/lrf
Date: November 15, 2012
LARIVIERE, GRUBMAN & PAYNE, LLP
(831) 649-8800

Claims and Subject Matter Support Mapping

58. A method of preventing confusion in users of a multiple outlet power strip having several identical outlets for providing power to a plurality of devices [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figures 2 and 3] comprising the steps of:

- a. assigning a separate and distinct color code to each outlet for selectively identifying each outlet of said power strip [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figures 2 and 3, reference characters C1, C2, C3 etc.]; and
- b. assigning to each color-coded outlet a different color from any other such color-coded outlet [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figures 2 and 3, reference characters C1, C2, C3 etc.]; and
- c. providing colored indicia adjacent to each color-coded outlet, wherein each indicia comprises a background color identical to its adjacent color-coded outlet. [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figure 3, reference characters I_{C1}, I_{C2}, I_{C3} etc.].

59. The method, as recited in claim 58, wherein each indicia identifies a peripheral device connected to the adjacent color-coded outlet.

60. The method, as recited in claim 58, wherein each indicia comprises a color-coded label identifying the peripheral device connected to the adjacent color-coded.

61. The method, as recited in claim 58, wherein each color-coded label comprises a unique identifier to identify a peripheral device.

62. A method, as recited in claim 58, wherein the unique identifier comprises one or more printed words and/or abbreviations thereof .

63. An electrical power distribution system comprising:

- a. a housing having a plurality of substantially identical AC power distribution outlets for providing AC electrical power to a plurality of peripheral devices connected thereto [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figures 2 and 3, reference character 20N]; and
- b. a plurality of unique colored areas disposed on or proximate to each outlet, for identifying each outlet and the peripheral device connected to each outlet. [Support found on page 3, lines 11-25; page 3, line 29 through page 4, line 6; page 5, line 23 through page 7, line 8; and Figures 2 and 3, reference characters C1, C2, C3 etc. and I_{C1}, I_{C2}, I_{C3} etc.].

64. The electrical power distribution system of claim 63, further comprising:

- a. a plurality of color-coded labels located adjacent to the outlets, wherein each color-coded label:
 1. comprises the same color as the adjacent colored area; and
 2. identifies a peripheral device connected to the adjacent outlet.

65. The electrical power distribution system of claim 64 wherein each color-coded label comprises a unique identifier to identify the peripheral device.

66. The electrical power distribution system of claim 65 wherein the unique identifier comprises one or more printed words and abbreviations thereof.

67. The AC electrical power distribution system as recited in claim 66 further comprising overcurrent and noise protection elements.